



IN THE US PATENT AND TRADEMARK OFFICE

October 2, 2003

20/Appeal
Brief
Cheresa
10.29.03

Applicants: Rainer Ludwig

Title : MONITORING DEVICE

Serial No.: 09/758 513

Filed : Jan. 11, 2001

Group: 2837

Examiner: McCloud

Confirmation No. 8395

Commissioner for Patents

P.O. Box 1450

Arlington, VA 22313-1450

APPELLANT'S NEW BRIEF ON APPEAL

Dear Sir:

In response to communication mailed September 18, 2003, Applicants submit APPELLANT'S NEW BRIEF ON APPEAL as an appeal from the decision of the Examiner dated January 2, 2003, finally rejecting claims 1, 3-10, and 39 and objecting to claims 11-38. Favorable consideration is requested.

REAL PARTY IN INTEREST

The real party in interest is MIDDEX-ELECTRONIC GmbH, the assignee of the entire right, title and interest in the above application.

RELATED APPEALS AND INTERFERENCES

There are no appeals or interferences known to Applicant or the undersigned which will directly affect, or be affected by or have a bearing on the Board's decision in the appeal. Copending applications Serial No. 09/758,514 and 09/758,515 of common inventorship, ownership and filing date herewith include certain depending claims which may be affected by the Board's decision on appeal (e.g. see claims 37-53 of Serial No. 09/758,514 and claims 20-36 of Serial No. 09/758,515 relating to a seal). Since these copending applications do not constitute prior art, Applicant proposes to obviate any possible double patenting rejection that may be raised by the claims of the above copending applications Serial No. 09/758,514 and Serial No. 09/758,515 by terminal disclaimer, if necessary, following a decision on patentability of rejected claims 1, 3-10 and 39 herein.

RECEIVED
OCT - 9 2003
TECHNOLOGY CENTER 2837

STATUS OF CLAIMS

Claims 1 and 3-39 are pending herein and claim 2 is canceled. Claims 1, 3-10, and 39 are finally rejected and are the claims on appeal. Claims 11-38 are objected to and indicated to contain allowable subject matter. The pending claims 1 and 3-39 appear in the Appendix.

STATUS OF AMENDMENTS

A response to the final rejection was filed and entered.

SUMMARY OF THE INVENTION

Applicants' invention as defined by independent claim 1 is directed to a monitoring device for checking for a predefined position of a body or for checking for the presence of a body wherein the device comprises a pivotal checking element with a motor for driving it, a housing for the motor, and a seal which is arranged between the checking element and the housing and which extends around a shaft by means of which the checking element is driven, the seal abutting on the checking element and on the housing (see specification page 1, lines 1-5 and lines 27-30; page 10, lines 1-16; and page 11, lines 16-26 and page 11, lines 34-37 and housing 12, motor 20, shaft 22, checking element 52 and seal 68 of Figures 1-3).

Claim 3 depends from claim 1 and includes the seal being formed symmetrically about an axis (see page 2, lines 30-31 and seal 68 of Figure 1).

Claim 4 depends from claim 1 and includes the seal being seated between the checking element and the housing co-axially relative to the shaft (see page 3, lines 1-3 and seal 68 of Figure 1).

Claim 5 depends from claim 1 and includes an intermediate space formed between the shaft and the seal (see page 3, lines 4-6 and space 69 of Figure 1).

page 3 USSN 09/758 513

Claim 6 depends from claim 1 and includes the seal being fixed on the checking element such that the seal rotates with the checking element relative to the housing (see page 3, lines 7-11 and seal 68 and checking element 52 of Figure 1).

Claim 7 depends from claim 6 and includes the checking element having a mounting element for the seal onto which the seal is disposed in order to fix the seal on the checking element for rotation therewith (see page 3, lines 23-29 and checking element 52, mounting element 64, and seal 68 of Figure 1).

Claim 8 depends from claim 7 and includes the mounting element being formed by a mounting ring through which the shaft is guided and onto which the seal is disposed (see page 3, lines 31-34 and mounting ring 64 of Figure 1).

Claim 9 depends from claim 8 and includes an annular recess provided for the seal between the mounting element and the checking element (see page 3, lines 35-36 through page 4, line 1 and recess 66 of Figure 1).

Claim 10 depends from claim 1 and includes an outer diameter of the seal substantially corresponding to the diameter of the checking element (see page 4, lines 7-11 and seal 68 of Figure 1).

Claim 11 depends from claim 1 and includes the seal comprising a packing ring disposed on the checking element (see page 4, lines 12-15 and packing ring 70 of Figure 2).

Claim 12 depends from claim 1 and includes the seal comprising a collar having a V-shaped sealing lip which abuts the housing (see page 4, lines 16-18 and seal collar 72 of Figures 2-3).

page 4 USSN 09/758 513

Claim 13 depends from claim 12 and includes the collar being rotatable with the checking element relative to the housing (see page 4, lines 25-26 and collar 72 of Figure 2).

Claim 14 depends from claim 12 and includes the collar outer surface being substantially in the form of a truncated cone at least when force is not being applied thereto in the axial direction (see page 4, lines 30-32 and collar 72 of Figure 2).

Claim 15 depends from claim 14 and includes an imaginary cone peak of the collar pointing towards the checking element (see page 4, lines 32-34 and seal 68 of Figure 1 and collar 72 of Figure 2).

Claim 16 depends from claim 14 and includes the inner surface of the collar being substantially in the form of a truncated cone at least when force is not being applied thereto in the axial direction (see page 5, lines 3-5 and collar 72 of Figures 2-3).

Claim 17 depends from claim 12 and includes an axial extent of the seal being varied by the collar (see page 5, 9-12 and seal 68 of Figures 1-3).

Claim 18 depends from claim 1 and includes a control device by means of which at least one of the pivotal position, the speed, and the torque of the checking element is controllable (see page 5, lines 13-15 and control device 50 of Figure 4).

Claim 19 depends from claim 18 and includes the control device controlling the pivotal position, the speed and the torque in combination (see page 5, lines 17-19 and device 50 of Figure 4).

Claim 20 depends from claim 18 and includes pivotal movement being controllable by the control device such that a maximum permissible torque will lie below a predefined torque value (see page 5, lines 20-22 and maximum permissible torque line 146 of Figure 5).

page 5 USSN 09/758 513

Claim 21 depends from claim 20 and includes the checking element being adapted to be pivoted from a starting position through a transition region into a monitoring region, and the predefined value for the maximum permissible torque in the monitoring region being reduced relative to that in the transition region (see page 6, lines 3-9 and positions 150, 142, 144 of Figure 6).

Claim 22 depends from claim 20 and includes an electric motor and the controlling of the maximum permissible torque being effected by limiting the supply of current to the motor (see page 6, lines 17-20 and motor 20 of Figure 1).

Claim 23 depends from claim 21 and includes the speed of the checking element being reducible during its transfer from the transition region into the monitoring region (see page 6, lines 26-28 and speed curve 148 of Figure 5 and regions 142, 144 of Figure 6).

Claim 24 depends from claim 23 and includes a reduction of the maximum permissible torque being effected after the reduction in the speed of the checking element (see page 6, lines 32-34 and torque line 146 and speed curve 148 of Figure 5).

Claim 25 depends from claim 21 and includes the transition region comprising an acceleration region (see page 7, lines 1-4 and transition region 142 of Figure 6).

Claim 26 depends from claim 21 and includes the transition region comprising a braking region (see page 7, lines 5-8 and transition region 142 of Figure 6).

page 6 USSN 09/758 513

Claim 27 depends from claim 21 and includes the speed of the checking element in the transition region being maintained substantially constant between an acceleration region and a braking region (see page 7, lines 9-12 and speed curve 148 of Figure 5 and region 142 of Figure 6).

Claim 28 depends from claim 21 and includes the speed of the checking element being maintained substantially constant in the monitoring region (see page 7, lines 23-25 and speed curve 148 of Figure 5).

Claim 29 depends from claim 18 and includes a digital angle transmitter for controlling the pivotal movement of the checking element (see page 7, 31-33 and digital transmitter 38 of Figure 4).

Claim 30 depends from claim 29 and includes both the speed and the torque of the checking element being controlled by the control device by time-dependent controlling of the position of the checking element (see page 8, lines 1-4 and speed curve 148 and torque line 168 of Figure 5).

Claim 31 depends from claim 29 and includes the control device setting the pivotal position of the checking element (see page 8, lines 10-11 and position line 172 of Figure 6).

Claim 32 depends from claim 29 and includes the control device setting the speed of the checking element (see page 8, lines 11-12 and speed curve 148 of Figure 5).

Claim 33 depends from claim 30 and includes the control device setting both the pivotal position and the speed of the checking element (see page 8, lines 15-19 and line 172 of Figure 6 and speed curve 148 of Figure 6).

page 7 USSN 09/758 513

Claim 34 depends from claim 21 and includes the control device being adapted to undergo a learning cycle for determining the monitoring region (see page 8, lines 20-21 and monitoring region 144 of Figure 6).

Claim 35 depends from claim 34 and includes the monitoring region being set by the control device such that it begins at a certain angular amount prior to the learnt position at which a body is detected in the learning cycle (see page 8, lines 27-30 and monitoring region 144 of Figure 6).

Claim 36 depends from claim 1 and includes stop means provided for limiting pivotal movement of the checking element (see page 9, lines 1-2 and stop pins 28 and 34 of Figure 1).

Claim 37 depends from claim 36 and includes that, for the purposes of setting a reference position of the checking element, the checking element is moved at a predefined speed to a stop position in which the stop means touch (see page 9, lines 5-9 and reference position 150 of Figures 5-6).

Claim 38 depends from claim 37 and includes that, for the purposes of defining the reference position of the checking element in the stop position, the stop means are rotated against each other at low torque (see page 9, lines 10-14 and reference position 150 of Figures 5-6).

Claim 39 is an independent claim and is similar to claim with the seal being arranged between the checking element and the end face of the housing and which extends around the shaft, wherein the seal abuts on the checking element and abuts on the end face of the housing (see page 1, lines 1-5 and lines 27-30; page 10, lines 1-16; and page 11, lines 16-26 and page 11, lines 34-37 and housing 12, motor 20, shaft 22, checking element 52 and seal 68 of Figures 1-3).

ISSUES

FIRST ISSUE

The first issue presented for review is whether the subject matter of claims 1 and 3-10 is anticipated under 35 USC 102(a) by the Huber US Patent 6 130 516.

SECOND ISSUE

The second issue presented for review is whether the subject matter of claim 39 is anticipated under 35 USC 102(a) by the Huber US Patent 6 130 516.

GROUPING OF THE CLAIMS

Claims 1 and 3-39 do not stand or fall together. Claims 1 and 39 are independent claims which are separately patentable since claim 39 further recites that the seal is arranged between the checking element and an end face of the housing and that the seal abuts on the checking element and abuts on the end face of the housing. Depending claim 3 is separately patentable from claim 1 in further reciting that the seal is formed symmetrically about an axis. Depending claim 4 is separately patentable from claim 1 in further reciting that the seal is seated between the checking element and the housing co-axially relative to the shaft. Depending claim 5 is separately patentable from claim 1 in further reciting that an intermediate space is formed between the shaft and the seal. Depending claim 6 is separately patentable from claim 1 in further reciting that the seal is fixed on the checking element such that the seal rotates with the checking element relative to the housing. Depending claim 7 is separately patentable from claim 6 in further reciting that the checking element comprises a mounting element for the seal onto which the seal is disposed in order to fix the seal on the checking element for rotation therewith. Depending claim 8 is separately patentable from claim 7 in further reciting that the mounting element is formed by a mounting ring through which the

page 9 USSN 09/758 513

shaft is guided and onto which the seal is disposed. Depending claim 9 is separately patentable from claim 8 in further reciting that an annular recess for accommodating the seal is formed between the mounting element and the checking element. Depending claim 10 is separately patentable from claim 1 in further reciting that an outer diameter of the seal substantially corresponds to the diameter of the checking element. Claims 11-38 are separately patentable over the claim or claims from which they depend in view of the examiner's indication that the subject matter of these claims is allowable.

ARGUMENT

FIRST ISSUE:

The rejection of claims 1 and 3-10 as anticipated under 35 USC 102(a) by the Huber US Patent 6 130 516 is in error.

The examiner argues that Huber teaches Applicant's monitoring device set forth in claim 1 and refers particularly to a seal of Huber located between a checking element (pin holder) 32 and a housing 16 in the area between reference numeral 28 and reference numeral 30 wherein that area allegedly abuts on the checking element (pin holder) 32 and on the end face of the housing 16.

The examiner is believed to be in error in construing the Huber '516 patent to anticipate Applicant's claim 1. In particular, the Huber '516 patent discloses a double lip seal 28 for sealing the passage of the shaft 26 through the face-sided cover of the housing 16 against chips and coolant (see patent column 2, lines 64-67) and O-rings seals 30 for sealing the respective face-sided cover of the housing 16 (see patent column 2, line 67 through column 3, line 1).

The area between reference numerals 28 and 30 referred to by the examiner as a seal in actuality comprises one end (i.e. one of the so-called face-sided covers) of the housing 16. In particular, at column 2, lines 64-67, Huber expressly states (1) that the double lip seal 28 "seals the passage of the shaft 26 through the face-sided cover of the housing 16 against chips and coolant" and (2) that "O-ring seals 30 seal the respective face-sided cover of the cylindrical housing 16". That is, the area between seals 28, 30 in actuality must be the face-sided cover of the housing 16 that is expressly described as being sealed by seals 28, 30 in the Huber patent and shown as being threadably secured at cooperating threaded regions in the housing 16 (also see corresponding German patent document DE 43 10 872 A1 submitted by Applicant).

At column 3, lines 1-5, the Huber patent expressly states that the pin holder 32 "is clamped via set screw 36 on the stump of the shaft 26 that projects beyond the housing 16". In the Huber patent, there is a space between the area between reference numerals 28, 30 referred to by the examiner (which actually is the face-sided cover of the housing) and the checking element (pin holder) 32 in order to allow the checking element to be pivoted by the motor 20. The examiner's allegation that the area between reference numerals 28, 30 abuts the housing 16 and the checking element 32 is incorrect. The Huber device is described at column 2, lines 64-67 such that the area must be the face-sided cover of the housing 16 threaded into the housing and not a seal like that recited in Applicant's claim 1 as pointed out above.

With respect to claim 3, the seals 28, 30 of the Huber are not arranged between the checking element (pin holder) 32 and the housing 16 and do not abut on both the housing and the checking element. As discussed above, the area between reference numerals 28, 30 must be the face-sided cover of the housing described at column 2, lines 64-67 and not a seal like that recited in Applicant's claim 3.

page 11 USSN 09/758 513

With respect to claim 4, the seals 28, 30 of the Huber patent are not arranged between the checking element (pin holder) 32 and the housing 16 and do not abut on both the housing and the checking element. As discussed above, the area between reference numerals 28, 30 must be the face-sided cover of the housing described at column 2, lines 64-67 and not a seal like that recited in Applicant's claim 4.

With respect to claim 5, the inner seals 28 of the Huber patent appear to abut on the shaft 26 such that there is no intermediate space between the shaft and seal as set forth in claim 5.

With respect to claim 6 reciting that the seal is fixed on the checking element such that the seal rotates with the checking element relative to the housing, the Huber patent expressly states (1) that the double lip seal 28 "seals the passage of the shaft 26 through the face-sided cover of the housing 16 against chips and coolant" and (2) that "O-ring seals 30 seal the respective face-sided cover of the cylindrical housing 16". The seal 28 is fixed in position between the shaft 26 and the face-sided cover that, in turn, is threaded into the housing 16. The seals 30 are fixed in position between the housing 16 and the face-sided cover that is threaded into the housing 16. Neither the seal 28 nor the seals 30 rotate(s) with the checking element (pin holder 32). As discussed above, the area between reference numerals 28, 30 is the face-sided cover that is fixed in position by being threaded into the housing 16 and does not rotate with the checking element (pin holder) 32.

With respect to claim 7, the Huber patent expressly states (1) that the double lip seal 28 "seals the passage of the shaft 26 through the face-sided cover of the housing 16 against chips and coolant" and (2) that "O-ring seals 30 seal the respective face-sided cover of the cylindrical housing 16". The seal 28 is fixed in position

page 12 USSN 09/758 513

between the shaft 26 and the face-sided cover threaded into the housing 16. The seals 30 are fixed in position between the housing 16 and the face-sided cover threaded into the housing 16. Neither the seal 28 nor the seals 30 is/are mounted on the pin holder 32 so as to rotate therewith.

With respect to claim 8, the examiner refers to reference numeral 32 as being a mounting element as set forth in claim 8. However, the Huber patent expressly states that reference numeral 32 designates the pin holder 32 that is rotated by motor 20. As discussed above, the area between seals 28, 30 in actuality is the face-sided cover of the housing 16 that is threaded into the housing and is expressly described as being sealed by seals 28, 30. This face-sided cover of the housing is not disposed on a mounting ring on the pin holder 32 and instead is part of the housing 16 as discussed above. Applicant does not understand how the area between seals 28, 30 (i.e. the face-sided cover of the housing) can be threadably mounted on the housing 16 as shown in the Huber patent and, at the same time, be mounted on the pivotable pin holder 32 as argued by the examiner. The examiner's argument flies in the face of the teachings of the Huber patent.

With respect to claim 9 which relates to an annular recess, there is no such annular recess provided on the pin holder 32 of the Huber patent.

Similarly, the Huber patent does not disclose the features of pending claim 10 which recites that an outer diameter of the seal substantially corresponds to the diameter of the checking element. The seals 28, 30 of the Huber patent teach away from claim 10. As discussed above, the area between seals 28, 30 in actuality is the face-sided cover of the housing 16 that is threaded into the housing and sealed by seals 28, 30.

page 13 USSN 09/758 513

SECOND ISSUE

The rejection of claim 39 as anticipated under 35 USC 102(a) by the Huber US Patent 6 130 516 is in error.

The examiner argues that Huber teaches Applicant's monitoring device set forth in claim 39 and refers particularly to a seal between a checking element (pin holder) 32 and a housing 16 in the area between reference numeral 28 and reference numeral 30 wherein that area allegedly abuts on the checking element (pin holder) 32 and on the end face of the housing 16.

The examiner is believed to be in error in construing the Huber '516 patent to anticipate Applicant's claim 39. In particular, the Huber '516 patent discloses a double lip seal 28 for sealing the passage of the shaft 26 through the face-sided cover of the housing 16 against chips and coolant (see patent column 2, lines 64-67) and O-rings seals 30 for sealing the respective face-sided cover of the housing 16 (see patent column 2, line 67 through column 3, line 1).

The area between reference numerals 28 and 30 referred to by the examiner as a seal in actuality comprises one end (i.e. one of the so-called face-sided covers) of the housing 16. In particular, at column 2, lines 64-67, Huber expressly states (1) that the double lip seal 28 "seals the passage of the shaft 26 through the face-sided cover of the housing 16 against chips and coolant" and (2) that "O-ring seals 30 seal the respective face-sided cover of the cylindrical housing 16". That is, the area between seals 28, 30 in actuality must be the face-sided cover of the housing 16 that is expressly described as being sealed by seals 28, 30 in the Huber patent and shown as being threadably secured at cooperating threaded regions in the housing 16.

page 14 USSN 09/758 513

At column 3, lines 1-5, the Huber patent expressly states that the pin holder 32 "is clamped via set screw 36 on the stump of the shaft 26 that projects beyond the housing 16". In the Huber patent, there is a space between the area between reference numerals 28, 30 referred to by the examiner (which actually is the face-sided cover of the housing) and the checking element (pin holder) 32 in order to allow the checking element to be pivoted by the motor 20. The examiner's allegation that the area between reference numerals 28, 30 abuts the housing 16 and the checking element 32 is incorrect.

The Huber device is described at column 2, lines 64-67 such that the area must be the face-sided cover of the housing 16 threaded into the housing and not a seal like that recited in Applicant's claim 39 as pointed out above.

CONCLUSION

FIRST ISSUE

It is respectfully submitted that pending claims 1 and 3-10 are not anticipated under 35 USC 102(a) by the Huber US Patent 6 130 516.

SECOND ISSUE

It is respectfully submitted that pending claim 39 is not anticipated under 35 USC 102(a) by the Huber US Patent 6 130 516.

Respectfully submitted,

IN TRIPLICATE

A handwritten signature in black ink, appearing to read "Edward J. Timmer", with a horizontal line underneath.

Edward J. Timmer Reg. No. 24 702

Walnut Woods Centre
5955 W. Main Street
Kalamazoo, MI 49009
Encl. Appendix and Postal Card

APPENDIX

1. A monitoring device for checking for a predefined position of a body or for checking for the presence of a body, comprising a pivotal checking element, a motor for driving the checking element, a housing for accommodating the motor, and a seal which is arranged between the checking element and the housing and which extends around a shaft by means of which the checking element is driven, wherein the seal abuts on the checking element and abuts on the housing.

3. A monitoring device in accordance with Claim 1, wherein the seal is formed symmetrically about an axis.

4. A monitoring device in accordance with Claim 1, wherein the seal is seated between the checking element and the housing co-axially relative to the shaft.

5. A monitoring device in accordance with Claim 1, wherein an intermediate space is formed between the shaft and the seal.

6. A monitoring device in accordance with Claim 1, wherein the seal is fixed on the checking element such that said seal rotates with said checking element relative to said housing.

7. A monitoring device in accordance with Claim 6, wherein the checking element comprises a mounting element for the seal onto which the seal is disposed in order to fix the seal on the checking element for rotation therewith.

8. A monitoring device in accordance with Claim 7, wherein the mounting element is formed by a mounting ring through which the shaft is guided and onto which the seal is disposed.

9. A monitoring device in accordance with Claim 8, wherein an annular recess for accommodating the seal is formed between the mounting element and the checking element.

page 2 USSN 09/758 513 - Appendix

10. A monitoring device in accordance with Claim 1, wherein an outer diameter of the seal substantially corresponds to the diameter of the checking element.

11. A monitoring device in accordance with Claim 1, wherein the seal comprises a packing ring disposed on the checking element.

12. A monitoring device in accordance with Claim 1, wherein the seal comprises a collar having a V-shaped sealing lip which abuts the housing.

13. A monitoring device in accordance with Claim 12, wherein the collar is rotatable with the checking element relative to the housing.

14. A monitoring device in accordance with Claim 12, wherein the outer surface of the collar is substantially in the form of a truncated cone at least when force is not being applied thereto in the axial direction.

15. A monitoring device in accordance with Claim 14, wherein an imaginary cone peak of the collar points towards the checking element.

16. A monitoring device in accordance with Claim 14, wherein the inner surface of the collar is substantially in the form of a truncated cone at least when force is not being applied thereto in the axial direction.

17. A monitoring device in accordance with Claim 12, wherein an axial extent of the seal can be varied by the collar.

page 3 USSN 09/758 513 - Appendix

18. A monitoring device in accordance with Claim 1, wherein a control device is provided by means of which at least one of the pivotal position, the speed, and the torque of the checking element is controllable.

19. A monitoring device in accordance with Claim 18, wherein the control device controls the pivotal position, the speed and the torque of the checking element in combination.

20. A monitoring device in accordance with Claim 18, wherein the pivotal movement is controllable by the control device in a manner such that a maximum permissible torque will lie below a predefined value for the torque.

21. A monitoring device in accordance with Claim 20, wherein the checking element is adapted to be pivoted commencing from a starting position through a transition region into a monitoring region in which the predefined position of the body lies or in which the presence of a body should be monitored, and the predefined value for the maximum permissible torque in the monitoring region is reduced relative to that in the transition region.

22. A monitoring device in accordance with Claim 20, wherein the motor is an electric motor and the controlling of the maximum permissible torque is effected by limiting the supply of current to the motor.

23. A monitoring device in accordance with Claim 21, wherein the speed of the checking element is reducible during its transfer from the transition region into the monitoring region.

page 4 USSN 09/758 513 - Appendix

24. A monitoring device in accordance with Claim 23, wherein the reduction of the maximum permissible torque is effected after the reduction in the speed of the checking element.

25. A monitoring device in accordance with Claim 21, wherein the transition region comprises an acceleration region in which the speed of the checking element is increased commencing from the starting position.

26. A monitoring device in accordance with Claim 21, wherein the transition region comprises a braking region in which the speed of the checking element is reduced.

27. A monitoring device in accordance with claim 21, wherein the speed of the checking element in the transition region is maintained substantially constant between an acceleration region and a braking region of the transition region.

28. A monitoring device in accordance with claim 21, wherein the speed of the checking element is maintained substantially constant in the monitoring region.

29. A monitoring device in accordance with Claim 18, wherein the control device comprises a digital angle transmitter for controlling the pivotal movement of the checking element.

30. A monitoring device in accordance with Claim 29, wherein the speed and the torque of the checking element are controlled by the control device by means of time-dependent controlling of the position of the checking element.

31. A monitoring device in accordance with Claim 29, wherein the control device sets the pivotal position of the checking element.

page 5 USSN 09/758 513 - Appendix

32. A monitoring device in accordance with Claim 29, wherein the control device sets the speed of the checking element.

33. A monitoring device in accordance with Claim 30, wherein the control device sets the pivotal position and the speed of the checking element.

34. A monitoring device in accordance with Claim 21, wherein the control device is adapted to undergo a learning cycle for determining the monitoring region.

35. A monitoring device in accordance with claim 34, wherein the monitoring region is set by the control device such that it begins at a certain angular amount prior to the learnt position at which a body is detected in the learning cycle.

36. A monitoring device in accordance with Claim 1, wherein stop means are provided for limiting pivotal movement of the checking element.

37. A monitoring device in accordance with claim 36, wherein, for the purposes of setting a reference position of the checking element, the checking element is moved at a predefined speed to a stop position in which the stop means touch.

38. A monitoring device in accordance with Claim 37, wherein, for the purposes of defining the reference position of the checking element in the stop position, the stop means are rotated against each other at low torque.

page 6 USSN 09/758 513 - Appendix

39. A monitoring device for checking for a predefined position of a body or for checking for the presence of a body, comprising a pivotal checking element, a motor having a shaft for driving the checking element, a housing for accommodating the motor and having an end face through which the shaft passes, and a seal which is arranged between the checking element and the end face of the housing and which extends around said shaft, wherein the seal abuts on the checking element and abuts on the end face of the housing.